

DataRemote 90X1

The 90X1 provides flexible connectivity options catering to diverse communication needs. With its 5G cellular/WAN Wired Router capabilities and automated internet failover, the device ensures all critical equipment previously connected or dependent on the Public Switched Telephone Network (PSTN) can communicate via the integrated ATA with enhanced line support.

The 90X1 leverages its integrated battery backup and UPS power output capabilities to ensure power is provided to the approved device in the event of a loss of power.

The 90X1's integrated ATA enhanced line features support Machine-to-Machine (M2M), analog wireline in-band voice, FAX, alarm signals, etc.

DataRemote's innovative solution delivers an always-on experience even during power or Internet outages providing unmatched reliability no matter the conditions.



Key Features & Capabilities



Voice Lines

VoIP module certified on key VoIP platforms for interoperability



Up to 48 HR Battery

Powerful 18-cell lithium battery for extended operation without A/C power



Cellular Internet

5G cellular primary failover internet for resilient internet connectivity



Location Services

GNSS to provide advanced location services



Enhanced Lines

DataRemote proprietary analog POTS replacement technology



Device Management Portal

ARA device management portal user interface and API for system integration



In-house Development

All software developed in-house for improved agility, security, and product quality



UPS Backup

Provides power from battery to external device (cordless phone, internet gateway, etc.)

Interfaces

- 5G Sub-6 GHz module - supports 5G NSA & SA
- Covers most mainstream carriers
- 8 x RJ-11 FXS ports with surge protection
- 3 x RJ-45 Ethernet
 - 1 x 2.5GbE WAN/LAN port(s)
 - 2 x 1GbE LAN Port(s)
- USB type-A port
- 2 x SIM card slots - 2FF
- 4x SMA antenna port(s) - 5G/LTE/GNSS
- UPS power output for approved devices
- LED status indicators & reset button

Power

- DC input 19VDC, 4A barrel plug
- AC power adapter
 - output: 19V, 3.3A
- UPS power output for approved devices
 - 12VDC, 3.0A
- Battery: 18 Cell 15Ah; Lithium-ion
- Internal battery standby: up to 48 Hours*
- Graceful shutdown (Sends battery Alert)

Environmental

- Operation temperature: 0° C to + 40° C
(32° F to 104° F)
- Storage temperature: -40° C to + 70° C
(-40° F to 158° F)
- Relative humidity: 10% to 90% non-condensing
- Height: 4.5"
- Depth: 6.00"
- Width: 9.8"

Cellular Specifications

Variant	RM520N-GL	
5G NR	5G NR NSA Bands SA Bands Sub-6 CA DL 4 x 4 MIMO UL 2 x 2 MIMO	3GPP Release 16 NSA/SA operation, Sub-6 GHz n1/n2/n3/n5/n7/n8/n12/n13/n14/n18/n20/n25/n26/n28/n29/n30/n38/n40/n41/n48/n66/n70/n71/n75/n76/n77/n78/n79 n1/n2/n3/n5/n7/n8/n12/n13/n14/n18/n20/n25/n26/n28/n29/n30/n38/n40/n41/n48/n66/n70/n71/n75/n76/n77/n78/n79 FDD + FDD, TDD + TDD, FDD + TDD 2CA n1/2/n3/n7/n25/n30/n38/n40/n41/n48/n66/n77/n78/n79 n38/n41/n48/n77/n78/n79
LTE	LTE Category LTE Bands DL 4 x 4 MIMO	DL Cat 19/ UL Cat 18 B1/B2/B3/B4/B5/B7/B8/B12/B13/B14/B17/B18/B19/B20/B25/B26/B28/B29/B30/B32/B34/B38/B39/B40/B41/B42/B43/B46(LAA)/B48/B66/B71 B1/B2/B3/B4/B7/B25/B30/B38/B40/B41/B42/B43/B48/B66
UMTS	WCDMA Bands	B1/B2/B4/B5/B8/B19

*Battery actual time may vary based on usage

Call Features

- Ring-down capable
- DTMF: in-band, out of band
- Audio support (G.711 & G.729)
- Echo cancellation (G.168)
- CPC - Calling Party Control
- E911 support with geo-location
- TTY/TRS capable
- Caller ID/CWCID
- 3-way conference
- Call hold, forwarding, transfer, waiting

Management Capabilities

- Developer API for device integration
- Secure/restricted web-based management
- Mass device management and provisioning
- Line status monitoring with alert capabilities

Optional Wired NAT Router

- SD-WAN
- QoS for VoIP
- IP Pass-through
- Port Forwarding
- DHCP server and client

Certifications

